

NOTE:

1 MATERIAL:

CONTACTS: BRASS
 INSULATOR: PBT+G.F UL 94V-0 BK
 SHELL : BRASS

BACK CUP: PBT+G.F UL 94V-0 BK

2.MECHANICAL:

35N MAX.
 WITHDRAWAL FORCE:10N MIN.
 DURABILITY:1500 CYCLES MIN.

3.ELECTRICAL:



CURRENT-MAX[AMPS] 1.5A
 VOLTAGE-MAX[VOLTS] 30V
 WITHSTANDING VOLTAGE 500V AC
 CONTACT RESISTANCE [OHMS] 30 MILLIOHMS MAX
 INSULATION RESISTANCE [OHMS] 1000 MEGOHMS MIN

4.PLATING:

SEE TABLE NICKEL OVER ALL PLATING

5.ENVIRONMENTAL

TEMPERATURE RANGE -55°C~+85°C

| | | | | | | | | | |
|--|-------|---|---------|--------|------|-------|------|------|------|
| -TOLERANCES- UNLESS OTHERWISE SPECIFIED | | Show Me CABLES <small>cables & connectors since 1995</small> | | | | | | | |
| | |   | | | | | | | |
| X.X | ±0.38 | X.X° | ±3.00° | APPD: | | | | | |
| X.XX | ±0.25 | X.XX° | ±1.00° | CHECK: | DATE | SCALE | UNIT | TYPE | PAGE |
| X.XXX | ±0.13 | X.XXX° | ±0.500° | DRAW: | | 1:1 | mm | Z | 1/1 |