

SPECIFICATION

INSULATOR : ABS ROHS

SCREW: STEEL

FINISHED : CHROMATE PLATED

TYPE OPTION:

320=GENDER CHANGER TYPE

(轉換接頭外殼)

PARTS OPTION

M/M= 4PCS SHORT SCREW ONLY

(公/公 4支短螺絲)

M/F=4PCS SHORT SCREW+2PCS HEX-NUT

(公/母 4支短螺絲+2個螺母)

F/F=4PCS SHORT SCREW+4PCS HEX-NUT

(母/母 4支短螺絲+4個螺母)

INSULATOR COLOR

B=BLACK (黑色)

G=GREY (灰色)


P=BEIGE (貝吉色)

C=METALIZED (電鍍)

M/M = 1,000 SET/CTN NW: 12.0KG GW: 13.0KG CUFT:2.43'

M/F = 1,000 SET/CTN NW: 13.5KG GW: 14.5KG CUFT:2.43'

F/F = 1,000 SET/CTN NW: 15.0KG GW: 16.0KG CUFT:2.43'

UNLESS OTHERWISE SPECIFIED TOLERANCE		 Show Me CABLES <small>cables & connectors since 1995</small>	
ANG.	±5°		
0.	±0.5		
.0	±0.3		
.00	±0.2	SCALE: AS SHOWN	UNIT: mm
DRAWN	TOM	03/05/09	DRAWN NAME:
CHECKED	ARVEN	03/05/09	
APPROVED	TONY	03/05/09	PRODUCT NO. 1210
REV.		DATE	FILE NAME: D-SUB9 TO D-SUB9

REV.	DESCRIPTION	DATE
A		03/05/09