



NOTES:

ELECTRICAL:

1. VOLTAGE RATING:125 VAC RMS
2. CURRENT RATING:1.5AMP
3. CONTACT RESISTANCE:100MILLIOHMS MAX
4. INSULATION RESISTANCE:1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH:750 VAC RMS 60Hz, 1MIN

ENVIRONMENTAL:

1. STORAGE:-40° TO+85°
2. OPERATION:0° TO70°

MECHANICAL:

1. HOUSINGG MATERIAL:STAINLESS STEEL
2. INSERT MATERIAL:FAME RETARDANCY PBT
3. PCB MATERIAL:FR-4 T=1.6mm
4. CONTACT MATERIAL:PHOSPHOR BRONZE
STAMP PIN T=0.30mm
5. RJ45 JACK ;IFE:750 TIMES MIN
6. SHIELD MATERIAL: STAINLESS STEEL,
T=0.2mm

						Material				Part No.	15-660-180 SH
SYM		Number	Bill No. of Alteration	Signature	Date	Angles Projection	Size	Scale	Unit	Title:	
Drawn	Ding jian bo	2015.12.29			Tolerance		A4	X:1	mm	Cat6a RJ45 Shielded Keystone Coupler	
Checked	Ge pei jun	2015.12.29			ERP						
Approved	Wang wei jun	2015.12.29			Sheet					1 OF 1	Version: A/0
					0.00-20.00 ±0.10						
					20.00-50.00 ±0.15						
					50.00-100.00 ±0.20						
					100.00- ±0.25						
					Angle ±30°						