

**NOTES:**

**ELECTRICAL:**




1. VOLTAGE RATING:125 VAC RMS
2. CURRENT RATING:1.5AMP
3. CONTACT RESISTANCE:100MILLIOHMS MAX
4. INSULATION RESISTANCE:1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH:750 VAC RMS 60Hz, 1MIN

**ENVIRONMENTAL:**

1. STORAGE:-40° TO +85°
2. OPERATION:0° TO 70°

**MECHANICAL:**

1. HOUSING MATERIAL:PA66
2. INSERT MATERIAL:FAME RETARDANCY PBT
3. PCB MATERIAL:FR-4 T=1.6mm
4. RJ45 JACK CONTACT: PHOSPHOR BRONZE WITH NICKEL PATING GOLD PLATED (3U/6U/15U/30U/50U)
5. RJ45 JACK LIFE:750 TIMES MIN
6. Waterproof grade:IP68

											
										Item No.	15-710-001
										Part Name	waterproof RJ45 in-line coupler, Cat6 shielded type
										ERP Part No.	
SYM	Number	Bill No.of Alteration	Signature	Date	Material	Angles Projection	Size	Scale	Unit		
Drawn	Kevin	2019.3.5					A4	X:1	mm		
Approved	Wang wei jun	2019.3.5					Sheet	1 OF 1	Version: A/0		
				Tolerance							
				0.00-20.00 ±0.10							
				20.00-50.00 ±0.15							
				50.00-100.00 ±0.20							
				100.00- Angle ±0.25							
				±0.30							