



|                 |           |
|-----------------|-----------|
| ITEM NO:        | LENGTH"L" |
| 10S6-10100-0.5M | 500mm     |
| 10S6-10100-1M   | 1000mm    |

9A80

| P1 | P2       |
|----|----------|
| 1  | 1 SHIELD |
| 2  | 2 WHITE  |
| 3  | 3 WHITE  |
| 4  | 4 SHIELD |
| 4  | 4 SHIELD |
| 5  | 5 WHITE  |
| 6  | 6 WHITE  |
| 7  | 7 SHIELD |

\* NOTE: All relevant materials are complied with RoHS directive .

| No. | DESCRIPTION   | Q'TY   | Supplier     |
|-----|---|--------|--------------|
| 3   | MOLDED PE COLOR TRANSPARENT<br>MOLDED PVC BLACK                                   |        | M777<br>M304 |
| 2   | UL2725 SERIAL ATA EXTERNAL CABLE, (26AWG*2C+AM+2D)*2F<br>OD 2.2*7.6mm, JACKET RED | L-15mm | M299         |
| 1   | SETIAL ATA CONNECTOR, MALE 7 PIN, BLACK PLASTIC                                   | 2      | M950         |

APPROVED  
CHECKED  
DESIGNER  
DRAWING  
DATE

木子  
2020.07.30  
陳瑞雯  
HU

**Show Me**  
**CABLES**  
an INFINIT@ brand

Cable Length  
Unless Other Spec.  
Tolerances:  
0 ~200mm ±10mm  
201~1000mm ±20mm  
1001 ~1500mm ±25mm  
1501~2100mm ±30mm  
2100mm↑ ±40mm