

AM	Cable	AF
1	$\mathbb{R} D$	1
2 —	WH	2
3	<u> </u>	3
4	BK D:	4
Shell-	Drain	Shell

ELECTRICAL TEST:

7C/0. 203CCA		XX /	7C/0. 127CCA		JACKET OD:4.5±0.2mm							
			0, 0, 12, 00,1	(5)	oute	er molding	BLACK PVC 45P					20g
Insulator:PVC 1.0±0.05			PE 4	V	laterial	amplifier					1PCS	
Color: RD, BK		Color:WH, GR	③ inner molding PE,Nature color							10g		
		2	Co	nnector	USB AM 4P PIN:G/F,SHELL:Nickel plating							
Draid: 1C/0. 254CCS Shield: AL-Foil Show Me C A B L E S an INFINIT® brand				1	① Connector USB AF 4P PIN:G/F,SHELL:Nickel plating							1PCS
				NO.	NO. PART NAME DESCRIPTION							UNIT
				DESCRI	PTION	FINISHED	PRODUCT'S FIGURE SCALE FIT UNITS: MM				MM 1R	D ANGLE
				Title		B 2.0 Extensi nale- Active-	on Cable- A- Male/A- 16 FT	\triangle		1		
APPROVED	CHECKED	DRAWING	DESIGNED	Part No:		23	-109-065					
		YAN	YAN	FINISHING				\triangle	202	0/11/0	4	A1
				MATERIAL				SYM	[DATE	RE	VISION
		ı				1		QR-	025 2	007. 05	. 03.	A1

CONSUMER ITEM LENGTH(mm)