

## Construction & Dimenstions

CONDUCTOR PARAMETERS	
Number Of Conductors	2
AWG Size	16
Conductor Stranding	19x29
Conductor Type	Bare copper
Nominal DCR	4.2 Ohm/1000ft
Cabling Lay Length	3 in
Twists / Foot	4 twist/ft
INSULATION PARAMETERS	
Insulation Type	Plenum PVC
Insulation Thickness	0.008 in
Insulation Color Code	1. Black 2.Red
SHIELDING PARAMETERS	
Shield Type	None
ELECTRICAL CHARACTERISTICS	
-	

## Overall Construction

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	Flexible Plenum
Jacket Thickness	0.015 in
Nominal Cable O.D.	0.176 in
Plenum	Yes
NEC UL Rating	CMP
RoHS Compliant	Yes
Pull Tension	54 lbs
Bend Radius	1.583 in
Cable Weight	25 lbs

## Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	NFPA 262 Plenum
Operating Range	-0 to 60 Deg C
UL Voltage Rating	300

Product Photo



**Show Me**  
CABLES

an INFINIT® brand

www.showmecables.com  
888-519-9505 | sales@showmecables.com

Title

2 Conductor- 16 AWG- Stranded-  
Unshielded- Plenum

Part Number

25225BGY

Notes

1. Unless otherwise specified all dimensions are nominal
2. All specifications are subject to change without notice at any time
3. Dimensions are in millimeters