


Product Photo




Available Cable Types
SMC-195 Low Loss 50 Ohm Coax Cable

Heat Shrink



Heat Shrink



Attenuation and Average Power

MHz	dB/100 FT	dB/100 M	Av. Power (kW)
30	2	6.5	.89
50	2.5	8.4	.68
150	4.4	14.6	.39
220	5.4	17.7	.32
450	7.8	25.5	.22
800	10.5	34.3	.16
900	11.1	36.5	.15
1500	14.5	47.7	.12
1800	16	52.5	.11
2000	16.9	55.4	.10
2200	17.8	58.3	.09
2400	18.6	61.1	.09
2500	19	62.4	.09
3500	22.7	74.7	.07
5800	29.9	98.1	.06

Electrical Specifications

Cutoff Frequency	41GHz
Peak Power	2.5 kW
Velocity of Propagation	80%
Impedance	50Ω
Capacitance	24.3 pF/ft
DC Resistance - Inner	7.6 Ω/km
DC Resistance - Outer	4.9 Ω/km
Shielding Effectiveness	>90 dB
Jacket Spark	2500 Volts

- Available Connector Types**
- BNC Male / Female
 - FME Male / Female
 - MCX Male
 - N Male / Female
 - SMA Male / Female
 - RPSMA Male / Female
 - TNC Male / Female
 - RPTNC Male / Female
 - UHF Male / Female

- Available Form Factors**
- Straight
 - Right Angle
 - Bulkhead

- Available Connector Types**
- BNC Male / Female
 - FME Male / Female
 - MCX Male
 - N Male / Female
 - SMA Male / Female
 - RPSMA Male / Female
 - TNC Male / Female
 - RPTNC Male / Female
 - UHF Male / Female

- Available Form Factors**
- Straight
 - Right Angle
 - Bulkhead



www.showmecables.com
888-519-9505 | sales@showmecables.com

Title
Reverse Polarity TNC Male to Reverse Polarity TNC Male Low Loss 195 Coaxial Assembly

Part Number
28-114-XXX

Notes
1. Unless otherwise specified all dimensions are nominal
2. All specifications are subject to change without notice at any time
3. Dimensions are in millimeters