



NOTES:

ELECTRICAL:

1. VOLTAGE RATING:125 VAC RMS
2. CURRENT RATING:1.5AMP
3. CONTACT RESISTANCE:100MILLIOHMS MAX
4. INSULATION RESISTANCE:1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH:750 VAC RMS 60Hz, 1MIN

ENVIRONMENTAL:

1. STORAGE:-40° TO +85°
2. OPERATION:0° TO 70°

MECHANICAL:

1. HOUSING MATERIAL:ABS
2. PCB MATERIAL:FR-4 T=1.0mm
3. CONTACT MATERIAL:PHOSPHOR BRONZE
STAMP PIN T=0.30mm
4. RJ45 JACK ;IFE:750 TIMES MIN

SYM	Number	Signature	Date
Drawn			2015. 12. 11
Checked			2015. 12. 11
Approved			2015. 12. 11

Tolerance	
0.00-20.00	±0.10
20.00-50.00	±0.15
50.00-100.00	±0.20
100.00- Angle	±0.25 ±30°

Show Me CABLES <small>cables & connectors since 1995</small>					
Material		ABS		Item No.	3252
Angles Projection		Size	Scale	Unit	Part Name Cat6a RJ45 Shielded Inline Coupler
		A4	X:1	mm	
		Sheet	1 OF 1	Version: A/0	ERP Part No.