

1. VOLTAGE RATING:

DIELECTRIC VOLTAGE WITHSTAND TEST: 2000V/1 SECOND CONDUCTOR RESISTANCE: ≤9.06 \(\Omega/1000\) METERS **VOLTAGE RATING: AC 300/500V** 

- 2. CABLE MARKING:
  - CCC A133679 60227 IEC 53 (RVV) 300/500V 3×1.5MM<sup>2</sup>.
- 3. OPTIONAL LABELS MAY INCLUDE UL, CURRENT AND/OR WARNING.
- 4. CABLE ASSEMBLIES SHALL BE INDIVIDUALLY PACKAGED.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

# UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [ ] ARE MILLIMETERS

#### TOLERANCES:

 $.X = \pm .2$  [5.08] FRACTIONS  $.XX = \pm .02$  [.51] ± 1/32 ANGLES ± 1° .XXX = ±.005 [ .13 ]

## CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0

ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY

# Show Me CABLES

### an INFINIT® brand

115 Chesterfield Industrial Blvd., Chesterfield, MO 63005

Phone: 1.888.519.9505 Fax: 1.888.519.9515 Website: www.ShowMeCables.com E-mail: CustomerService@ShowMeCables.com

CAGE CODE DRAWN BY



THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF SHOWMECABLES, INC ALL RIGHTS RESERVED.

SCALE N/A

REV

Α

ITEM NO. 3SVT8 AKRESOWSK 44-451-02M