


		REVISION	
LTR	DESCRIPTION	DATE	APPROVED
A	NEW RELEASE	05/18/94	H.T.




CN36 Female




Specification:

1. Voltage Rating: 300 VAC(rms).
2. Current Rating: 5 AMP Continuous.
3. Dielectric Strength: 1,000 VAC.
4. Insulation Resistance: 5,000 Mohm min.
5. Durability: 30 Cycles for Gold Flash,
150 Cycles for 15u Gold Plated.
6. Corrosion Resistance: Meet MIL-STD-202F Method
101 Condition B Salt Water. Spray for Gold Plated Over 15u.
7. Mating Force Insertion Force: 1 oz – 16 oz
Average 150 gram. Extraction Force: 1 KG min.



CN36 Female

UNLESS OTHERWISE SPECIFIED: 1. DIMENSION ARE IN INCHS 2. TOLERANCES: DECIMALES X.XX ±0.25 3. DO NOT SCALE DRAWING 4. REMOVE ALL BURRS AND BREAK SHARP EDGES.	CUSTOMER				
	R.F.Q. NO.				
	DRAWN DATE	TITLE			
	CHECKED	Howie Tseng 05/18/94	CN36, F/F, Mini Gender Changer		
PROPRIETARY DOCUMENT THIS DRAWING AND/OR INFORMATION OR SUBJECT MATTER CONTAINED HEREIN, SHALL NOT BE USED, COPIED OR DISSEMINATED IN ANY MANNER, OR FOR ANY PURPOSE, OTHER THAN AS EXPRESSLY STATED BY COMTOP Enterprises Corp.	CUSTOMER APPROVAL	SIZE	DWG NO.	PART NO.	REV.
			31C1-104	31C1-10400	A
		SCALE: NONE	RELEASE DATE: 05/18/94	SHEET: 1	DF 1