

6

5

4


3

2

1

REVISION

ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	INITIAL RELEASE	02/08/2024	AKRESOWSKI	GUTTADAURO



NOTES:

- MATERIAL:**
 CABLE: 24 AWG, 2 CONDUCTORS,
 PVC JACKET OD: .138 ±.006 [3.5 ±0.15]
 MARKING: AWM 2464 80°C 300V 24AWG*2C VW-1
 P1 PLUG: USB-A MALE, NICKEL PLATED SHELL,
 INSULATOR COLOR: WHITE
 MOLDED PVC BOOT.
 P2 PLUG: DC Ø3.5 X 1.35 mm MALE, RIGHT ANGLE,
 NICKEL PLATED SHELL,
 INSULATOR COLOR: BLACK
 MOLDED PVC BOOT.
- ELECTRICAL TEST:**
 100% OPEN SHORT AND MISS WIRE TEST.
 CONDUCTIVE RESISTANCE: 0.2 Ω MAX.
 INSULATION RESISTANCE: 10 MΩ MIN AT 300V DC.

REGULATORY COMPLIANCE:
 EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION).

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED
 LEADING DIMENSIONS ARE INCHES
 DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:
 .X = ±.2 [5] FRACTIONS ± 1/32
 .XX = ±.02 [0.5] ANGLES ± 1°
 .XXX = ±.005 [0.13]

CABLE LENGTH TOLERANCES:
 ≤12 [305] = +1 [25] / -0
 >12 [305] ≤ 60 [1524] = +2 [51] / -0
 >60 [1524] ≤ 120 [3048] = +4 [102] / -0
 >120 [3048] ≤ 300 [7620] = +6 [152] / -0
 >300 [7620] = +5% / -0

ALL DIMENSIONS ARE FOR REFERENCE ONLY
 AND SUBJECT TO CHANGE WITHOUT NOTICE.
 UN-DIMENSIONED/NON-CRITICAL FEATURES
 MAY VARY IN SIZE AND LOCATION
 COLORS MAY VARY

Show Me™
CABLES

an INFINIT® brand

Website: www.ShowMeCables.com
 Phone: 1.888.519.9505



INTERPRET ALL DIMENSIONS AND
 TOLERANCES PER ASME Y14.5

SCALE SHEET

NONE 1 OF 1

DESCRIPTION

DC CA, USB to RA 3.5mm/1.35mm M, 3 FT

SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	3SVT8	AKRESOWSKI	55-172-XXX	A

6

5

4

3

2

1