



**EZ-RJ45 Cat6 Feed Through Connector-8P8C- Solid Stranded Cable**

Part No: 575

**SPECIFICATIONS**

1. ELECTRICAL:
  - UL APPLICATIONS: 250 VOLTS AC MAX. AT 2 AMPS.
  - DIELECTRIC WITHSTANDING VOLTAGE : 1000 VOLTS AC. 60 SEC.
  - INSULATION RESISTANCE: 500 MΩ.
  - CONTACT RESISTANCE: 20mΩ MAX.
2. MECHANICAL:
  - STRAIN RELIEF: 20 POUND MIN.
  - DURABILITY: 1200 MATING CYCLES.
3. MATERIAL:
  - HOUSING: POLYCARBONATE, UL94V-0 OR UL94V-2.
  - COLOR: TRANSPARENT OR OTHER COLOR ARE AVAILABLE.
  - CONTACT BLADE: COPPER ALLOY.
  - GOLD PLATING: 50u".
4. USAGE:
  - SUITABLE FOR STRANDED & SOLID WIRE 23AWG ~ 26 AWG.
  - (It can be used for the wire OD from Ø 0.93 ~ Ø1.04 , cable OD under 6.5mm)
5. Feed Through CAT6 8X8 RJ45 Modular Plug, for Round Solid / Stranded Cable, 3Prongs ,50u(UL)

BLADE:	E	EB	Y	YB	Z	A	AE	AB	EC
Drawing									
Mark					✓				
GOLD PLATING	3Mu"	3u"	6u"	15u"	30u"	50u"			
Mark							✓		