

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	2
• AWG Size	18
• Conductor Stranding	Solid
• Conductor Type	Bare Copper
• Nominal DCR	6.5 Ohm/1000ft
• Cabling Lay Length	3 in
• Twists/Foot	4 twist/ft
INSULATION PARAMETER	-
• Insulation Type	Plenum PVC
• Insulation Thickness	0.008 in
• Insulation Color Code	1. Black 2.Red
SHIELDING PARAMETER	-
• Shield Type	Overall 100% Aluminum Foil
• Drain Wire Type	Tinned Copper
• Drain Wire AWG	24 AWG
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	66 pF/ft
• Nom. Cap. Conductor to Shield	119 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	Flexible Plenum
Jacket Thickness	0.015 in
Nominal Cable O.D.	0.148 in
Plenum	Yes
NEC UL Rating	FPLP
RoHS Compliant	Yes
Pull Tension	53 lbs
Bend Radius	1.33 in
Cable Weight	22 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	NFPA 262 Plenum
Operating Range	-0 to 60 Deg C
UL Voltage Rating	300

Product Photo



Show Me
CABLES
 an INFINIT[®] brand
www.showmecables.com
 888-519-9505 | sales@showmecables.com

Title

2 Conductor- 18 AWG- Solid- Shielded
 -Fire Retardant- Plenum- Red

Part Number

60975BRD

Notes

1. Unless otherwise specified all dimensions are nominal
2. All specifications are subject to change without notice at any time
3. Dimensions are in millimeters