

## Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	2
• AWG Size	12
• Conductor Stranding	Stranded
• Conductor Type	Bare Copper
• Nominal DCR	1.8 Ohm/1000ft
• Cabling Lay Length	4 in
• Twists/Foot	3 twist/ft
INSULATION PARAMETER	-
• Insulation Type	Plenum PVC
• Insulation Thickness	0.09 in
• Insulation Color Code	1. Black 2.Red
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	40 pF/ft

## Product Photo



## Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	Flexible Plenum
Jacket Thickness	0.015 in
Nominal Cable O.D.	0.239 in
Plenum	Yes
NEC UL Rating	FPLP
RoHS Compliant	Yes
Pull Tension	159 lbs
Bend Radius	2.151 in
Cable Weight	55 lbs

## Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	NFPA 262 Plenum
Operating Range	-0 to 60 Deg C
UL Voltage Rating	300

**Show Me**

CABLES

an INFINIT® brand

www.showmecables.com

888-519-9505 | sales@showmecables.com

Title

2 Conductor- 12 AWG- Stranded-  
Unshielded - Fire Retardant-  
Plenum- Red

Part Number

60995BSRD

Notes

1. Unless otherwise specified all dimensions are nominal
2. All specifications are subject to change without notice at any time
3. Dimensions are in millimeters