

6

5

4

3

2

1

| REVISION | | | | | |
|----------|-----|-----------------|------------|------------|------------|
| ZONE | REV | DESCRIPTION | DATE | CHANGED BY | APPROVED |
| | A | INITIAL RELEASE | 02/01/2024 | SREITER | GUTTADAURO |

F

F

E

E

D

D

C


C

B

B

A


A




P1
PIN1
2X RJ45 SHIELDED PLUG
GOLD PLATED CONTACTS

2X SNAGLESS BOOT
LSZH, BLACK

2X L-COM LOGO
BOTH SIDES



CAT 7 SHIELDED MODULAR CABLE
FOUR TWISTED PAIR WITH ALUMINUM/ POLYESTER FOIL SHIELDING OF EACH PAIR
CONDUCTORS: 26 AWG STRANDED COPPER
OVERALL SHIELD: TINNED COPPER BRAID
JACKET: LOW SMOKE ZERO HALOGEN, COLOR: GRAY, NOM. DIA. .236 [6.0]
(OPERATING TEMPERATURE: -10°C TO +80°C; VOLTAGE RATING: 30V)



NOTES:

- 1.LSZH CABLE CHARACTERISTICS:
FLAME RATING: IEC 60332-1
CORROSIVE GAS: IEC 60754
SMOKE EMISSION: IEC 61034
- 2.LENGTHS OVER 10 METERS (32.8 FT) ARE CHANNEL RATED.
- 3.PLUG CONFORMS TO TIA-1096.
- 4.CABLE ASSEMBLY TO BE TESTED FOR CONTINUITY.
- 5.CABLE ASSEMBLY TO BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

| PART NUMBER | LENGTH METERS[FEET] |
|-------------|---------------------|
| 726Z-0.5 GY | 0.5[1.64] |
| 726Z-01 GY | 1.0[3.28] |
| 726Z-02 GY | 2.0[6.56] |
| 726Z-03 GY | 3.0[9.84] |
| 726Z-05 GY | 5.0[16.41] |
| 726Z-7.5 GY | 7.5[24.61] |
| 726Z-10 GY | 10.0[32.81] |
| 726Z-15 GY | 15.0[49.21] |

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

| | |
|---------------------|------------------|
| X = ±.2 [5] | FRACTIONS ± 1/32 |
| .XX = ±.02 [0.5] | ANGLES ± 1° |
| .XXX = ±.005 [0.13] | |

CABLE LENGTH TOLERANCES:

| | |
|--------------------------|-----------------|
| ≤12 [305] | = +1 [25] / -0 |
| >12 [305] ≤ 60 [1524] | = +2 [51] / -0 |
| >60 [1524] ≤ 120 [3048] | = +4 [102] / -0 |
| >120 [3048] ≤ 300 [7620] | = +6 [152] / -0 |
| >300 [7620] | = +5% / -0 |

ALL DIMENSIONS ARE FOR REFERENCE ONLY AND SUBJECT TO CHANGE WITHOUT NOTICE. UN-DIMENSIONED NON-CRITICAL FEATURES MAY VARY IN SIZE AND LOCATION. COLORS MAY VARY.

Show Me
CABLES
an INFINIT® brand

Website: www.ShowMeCables.com
Phone: 1.888.519.9505

INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5

| | |
|-------|--------|
| SCALE | SHEET |
| NONE | 1 OF 1 |

DESCRIPTION: CA,CAT7 S/FTP RJ45 TO RJ45 LSZH JKT, GRY

| | | | | |
|------|-----------|----------|------------|-----|
| SIZE | CAGE CODE | DRAWN BY | ITEM NO. | REV |
| A | 3SVT8 | SREITER | 726Z-XX GY | A |

6

5

4

3

2

1