

Show Me

C A B L E S

cables & connectors since 1995

Cat5e UTP Solid Outdoor PE Cable-Black

SKU: 85-500-245 BK:100

Category 5E Outdoor UTP 24 AWG 4 Pair 8 Solid Bare Copper Conductors, Black UV CMX PVC Jacket 1000FT (UL/ETL)

Applications

- 10/100/1000Base-T
- 100Base-VG
- 155 Mbps and 622-Mbps ATM
- Other high-performance applications
 - Aerial Applications
 - Outdoor Applications
 - Antennas

Compliance

- ISO/IEC 11801
- TIA/EIA-568-C.2 Category 5e
- ANSI/ICEA S-90-661 Category 5e
- NEMA WC63.1 Category 5e
- UL Listed
- ETL Verified
- RoHS Compliance for the Requirement of European Union Issued Directive 2002/95/EC

Physical Characteristics

- Conductor Size: 24AWG
- Conductor Material: Solid Bare Copper
- Insulation Material: High Density Polyethylene (HDPE)
- Insulation Diameter: 0.87 ± 0.03mm
- Number of Conductors: 8 Conductors
- Number of Pairs: 4 Pairs
- Outer Shield Material: N/A
- Drain Wire: N/A
- Outer Jacket Material: CMX PVC
- Outer Jacket Diameter: 5.0mm ± 0.4mm
- Outer Jacket Rip Cord: Yes

Pair Color Code Chart


- Pair 1 ----- White/Blue Stripe & Blue
- Pair 2 ----- White/Orange Stripe & Orange
- Pair 3 ----- White/Green Stripe & Green
- Pair 4 ----- White/Brown Stripe & Brown

Mechanical Characteristics

- Storage Temperature Range: N/A
- Installation Temperature Range: N/A
- Operating Temperature Range: N/A
- Bulk Cable Weight: N/A / 1000FT
- Max. Recommended Pulling Tension: N/A
- Min. Bend Radius/Minor Axis: N/A
- Min. Bend/Installation: N/A
- Test Object: Jacket
- Test Material: PVC
- Before Tensile Strength: ≥13.5
 - Aging Elongation: ≥150
 - Aging Condition: 100°C x 24hrs x 7Days
- After Tensile Strength: ≥12.5
 - Aging Elongation: ≥125
 - Cold Bend: No Visible Cracks (-20°C ± 2°C x 4h



Technical Diagram



Available Jacket Colors

- Black Item# C5CMX-414BK
- Black Item# C5CMX-2029BKWS
- White Item# C5CMX-2267WH
- Beige Item# C5CMX-2899BG

Cable Features

- Tested to 350MHz.
- Meets or exceeds CAT5E TIA568C.2 standards.
- Cable is marked in descending order so you always know how much cable is left.
- Extra headroom provides room for growth.
- Low attenuation and power-sum crosstalk.

Construction Facts

- This Outdoor Cable has high density polyethylene insulation.
- Longitudinal rip cord for easy jacket opening.

Cable Put-Ups:

- Cable is supplied in 1000ft increments in a pull box or on a wooden spool.

Electrical Characteristics

- Nom. Mutual Capacitance: N/A
- Nominal Velocity of Propagation: N/A
- Maximum Delay: 537.60 @ 100MHz (ns/100m)
- Maximum Delay Skew: ≤ 45 (ns/100m)
- Maximum Conductor DC Resistance: 9.5 (@ 20°C OHm/100m)
- Maximum Operating Voltage - UL: N/A
- Maximum DCR Unbalanced: 5% (@ 20°C)
- Attenuation (Maximum)
 - 22.0dB/100m (328.1ft.) @ 100MHz
 - 44.9dB/100m (328.1ft.) @ 350MHz
- 1.0 - 100MHz Impedance: 100Ω ± 15%
- NEXT (Minimum)
 - 35.3dB/100m (328.1ft.) @ 100MHz
 - 27.1dB/100m (328.1ft.) @ 350MHz
- PS-NEXT (Minimum)
 - 32.3dB/100m (328.1ft.) @ 100MHz
 - 24.1dB/100m (328.1ft.) @ 350MHz
- Return Loss (Minimum)
 - 20.1dB/100m (328.1ft.) @ 100MHz
 - 16.0dB/100m (328.1ft.) @ 350MHz

Jacket Printing

E317493-018 (UL) C(UL) CMX 4PR 24AWG CAT5E UTP 350MHZ UV OUTDOOR ETL VERIFIED TO ANSI/TIA – 568-B.2 ZONE A B C D E F / DEVICES 1 2 3 4 5 6 7 8 9

Sequential foot markers on jacket.

CAT5E 350MHz Outdoor Solid Bulk Cable Electrical Specifications

Frequency MHz (Maximum)	ATT dB/100 m (328 ft.) (Maximum)	ACR dB/100 m (328 ft.) (Maximum)	DELAY ns/100 m (328 ft.) (Minimum)	NEXT dB/100 m (328 ft.) (Minimum)	PS-NEXT dB/100 m (328 ft.) (Minimum)	ELFEXT dB/100 m (328 ft.) (Minimum)	PS-ELFEXT dB/100 m (328 ft.) (Minimum)	Return Loss dB (Minimum)
1.0	2.0	N/A	570.00	65.3	62.3	63.8	60.8	20.0
4.0	4.1	N/A	552.00	56.3	53.3	51.8	48.8	23.0
8.0	5.8	N/A	546.73	51.8	48.8	45.7	42.7	24.5
10.0	6.5	N/A	545.38	50.3	47.3	43.8	40.8	25.0
16.0	8.2	N/A	543.00	47.2	44.4	39.7	36.7	25.0
20.0	9.3	N/A	542.05	45.8	42.8	37.8	34.8	25.0
25.0	10.4	N/A	541.20	44.3	41.3	35.8	32.8	24.3
31.25	11.7	N/A	540.44	42.9	39.9	33.9	30.9	23.6
62.5	17.0	N/A	538.55	38.4	35.4	27.9	24.9	21.5
100	22.0	N/A	537.60	35.3	32.3	23.8	20.8	20.1
155	28.1	N/A	536.90	32.4	29.4	20.0	17.0	18.0
200	32.4	N/A	536.50	30.8	27.8	17.8	14.8	17.4
300	41.8	N/A	536.10	29.3	26.3	14.3	11.3	16.5
350	44.9	N/A	535.90	27.1	24.1	12.9	9.9	16.0