


Product Photo



Product Description

- FRPVC
- Bare Copper Conductor
- UL Listed Type CMR, CL3R

Applications

- For use in security systems, intercom systems, sound/audio systems, access control, power-limited controls.

Specification

- CONDUCTOR: Bare copper
- INSULATION: Polyvinyl Chloride (PVC)
- JACKET: Polyvinyl Chloride (PVC), Gray
- STANDARDS: NEC: CMR (22-16 AWG), CL3R (14-12 AWG)
- TEMPERATURE: 75°C

Standard color is gray, other colors available. Most items available on spools or boxes except on larger O.D. products. Diameters and weights may vary among manufacturers. Paired conductors also available

Part No.	Conductor Size AWG	No. of Conductors	Voltage	Rating	Insulation	Insulation Thickness (in.)	Overall Jacket Thickness (in.)	Nom. O.D. (in.)	Approx. Wt. lb./1,000 ft.
AL-2202C-1-1N-09	22 (SOL)	2	300V	CMR	PVC	0.007	0.015	0.122	8
AL-2202C-2-1N-09	22	2	300V	CMR	PVC	0.007	0.015	0.120	11
AL-2203C-2-1N-09	22	3	300V	CMR	PVC	0.007	0.015	0.131	14
AL-2204C-2-1N-09	22	4	300V	CMR	PVC	0.007	0.015	0.142	16
AL-2204C-1-1N-09	22 (SOL)	4	300V	CMR	PVC	0.007	0.015	0.135	14
AL-2206C-2-1N-09	22	6	300V	CMR	PVC	0.007	0.015	0.170	24
AL-2208C-2-1N-09	22	8	300V	CMR	PVC	0.007	0.018	0.190	31
AL-2210C-2-1N-09	22	10	300V	CMR	PVC	0.007	0.020	0.210	39
AL-2212C-2-1N-09	22	12	300V	CMR	PVC	0.007	0.022	0.229	15
AL-2002C-2-1N-09	20	2	300V	CMR	PVC	0.008	0.015	0.148	21

Part No.	Conductor Size AWG	No. of Conductors	Voltage	Rating	Insulation	Insulation Thickness (in.)	Overall Jacket Thickness (in.)	Nom. O.D. (in.)	Approx. Wt. lb./1,000 ft.
AL-2003C-2-1N-09	20	3	300V	CMR	PVC	0.010	0.015	0.161	26
AL-2004C-2-1N-09	20	4	300V	CMR	PVC	0.010	0.018	0.178	26
AL-1802C-2-1N-09	18	2	300V	CMR	PVC	0.009	0.015	0.172	16
AL-1803C-2-1N-09	18	3	300V	CMR	PVC	0.009	0.015	0.187	30
AL-1804C-2-1N-09	18	4	300V	CMR	PVC	0.009	0.018	0.203	37
AL-1806C-2-1N-09	18	6	300V	CMR	PVC	0.009	0.020	0.226	52
AL-1808C-2-1N-09	18	8	300V	CMR	PVC	0.009	0.020	0.242	66
AL-1602C-2-1N-09	16	2	300V	CMR	PVC	0.009	0.018	0.198	30
AL-1604C-2-1N-09	16	4	300V	CMR	PVC	0.009	0.020	0.234	54
AL-1402C-2-1N-09	14	2	300V	CL3R	PVC	0.010	0.025	0.238	45
AL-1404C-2-1N-09	14	4	300V	CL3R	PVC	0.010	0.025	0.286	74
AL-1202C-2-1N-09	12	2	300V	CL3R	PVC	0.011	0.028	0.296	68



an INFINIT® brand

www.showmecables.com

888-519-9505 | sales@showmecables.com

Title

2 Conductor-12 AWG- Low Voltage- Stranded - Non- Shielded- PVC- Gray

Part Number

87-207-001

Notes

1. Unless otherwise specified all dimensions are nominal
2. All specifications are subject to change without notice at any time
3. Dimensions are in millimeters