

**Product Description**

- PVC
- Bare Copper Conductor
- UL Listed Type CMR, CL3R

**Applications**

- For use in security systems, intercom systems, sound/audio systems, access control, power-limited controls.

**Specification**

- CONDUCTOR: Bare copper
- INSULATION: Polyvinyl Chloride (PVC)
- JACKET: Polyvinyl Chloride (PVC), Gray
- STANDARDS: NEC: CMR (22-16 AWG), CL3R (14-12 AWG)
- TEMPERATURE: 75°C

Standard color is gray, other colors available. Most items available on spools or boxes except on larger O.D. products. Diameters and weights may vary among manufacturers. Paired conductors also available

Product Photo



<u>Part No.</u>	<u>Conductor Size AWG</u>	<u>No. of Conductors</u>	<u>Rating</u>	<u>Insulation</u>	<u>Insulation Thickness (in.)</u>	<u>Overall Jacket Thickness (in.)</u>	<u>Nom. O.D. (in.)</u>	<u>Approx. Wt. lb./1,000 ft.</u>
AL-2202C-2-1S-09	22	2	CMR	PVC	0.007	0.015	0.112	12
AL-2202C-1-1S-09	22 (SOL)	2	CMR	PVC	0.007	0.015	0.121	14
AL-2203C-2-1S-09	22	3	CMR	PVC	0.007	0.015	0.118	14
AL-2204C-2-1S-09	22	4	CMR	PVC	0.007	0.015	0.129	19
AL-2204C-1-1S-09	22 (SOL)	4	CMR	PVC	0.007	0.015	0.119	19
AL-2206C-2-1S-09	22	6	CMR	PVC	0.007	0.015	0.17	27
AL-2208C-2-1S-09	22	8	CMR	PVC	0.007	0.015	0.183	32
AL-2210C-2-1S-09	22	10	CMR	PVC	0.007	0.018	0.189	42
AL-2212C-2-1S-09	22	12	CMR	PVC	0.007	0.015	0.11	44
AL-2002C-2-1S-09	20	2	CMR	PVC	0.008	0.015	0.129	17

  

<u>Part No.</u>	<u>Conductor Size AWG</u>	<u>No. of Conductors</u>	<u>Rating</u>	<u>Insulation</u>	<u>Insulation Thickness (in.)</u>	<u>Overall Jacket Thickness (in.)</u>	<u>Nom. O.D. (in.)</u>	<u>Approx. Wt. lb./1,000 ft.</u>
AL-2003C-2-1S-09	20	3	CMR	PVC	0.008	0.015	0.15	20
AL-2004C-2-1S-09	20	4	CMR	PVC	0.008	0.015	0.11	23
AL-1802C-2-1S-09	18	2	CMR	PVC	0.008	0.015	0.15	25
AL-1803C-2-1S-09	18	3	CMR	PVC	0.008	0.015	0.16	29
AL-1804C-2-1S-09	18	4	CMR	PVC	0.008	0.015	0.177	37
AL-1806C-2-1S-09	18	6	CMR	PVC	0.008	0.015	0.224	55
AL-1808C-2-1S-09	18	8	CMR	PVC	0.008	0.015	0.259	66
AL-1602C-2-1S-09	16	2	CMR	PVC	0.009	0.015	0.174	30
AL-1604C-2-1S-09	16	4	CMR	PVC	0.009	0.015	0.212	58
AL-1402C-2-1S-09	14	2	CL3R	PVC	0.01	0.017	0.229	50
AL-1404C-2-1S-09	14	4	CL3R	PVC	0.01	0.017	0.261	67
AL-1202C-2-1S-09	12	2	CL3R	PVC	0.011	0.017	0.274	69



www.showmecables.com  
888-519-9505 | sales@showmecables.com

Title	Multi-Conductor Cable- 14AWG- 4 Conductor- Low- Voltage- Shielded-PVC-Gray
Part Number	87-207-006

Notes	<p>1. Unless otherwise specified all dimensions are nominal</p> <p>2. All specifications are subject to change without notice at any time</p> <p>3. Dimensions are in millimeters</p>
-------	---