

Product Description

- PVC
- Solid conductor
- FPLR, UL Listed

Applications

- For Use With All Power Limited Circuits In Fire Protective Signaling

Specification

- CONDUCTOR: Solid bare copper
- INSULATION: PVC
- JACKET: PVC with rip cord
- STANDARDS: NEC FPLR, UL Listed
- TEMPERATURE: 75°C



Power limited fire alarm and communications cable for riser or nonriser applications. Fire alarm, smoke detectors, signaling and fire-protective circuits. Call your local sales representative for specific requirements.

Part No.	Conductor Size AWG	No. of Conductors	Rating	Insulation	Insulation Thickness (in.)	Overall Jacket Thickness (in.)	Nom. O.D. (in.)	Approx. Wt. lb./1,000 ft.
FA-1202C-1-1N-03	12	2	FPLR	PVC	0.012	0.015	0.264	62
FA-1204C-1-1N-03	12	4	FPLR	PVC	0.012	0.015	0.258	80
FA-1402C-1-1N-03	14	2	FPLR	PVC	0.010	0.015	0.212	40
FA-1404C-1-1N-03	14	4	FPLR	PVC	0.010	0.015	0.252	73
FA-1602C-1-1N-03	16	2	FPLR	PVC	0.010	0.015	0.183	28
FA-1604C-1-1N-03	16	4	FPLR	PVC	0.010	0.015	0.216	49
FA-1802C-1-1N-03	18	2	FPLR	PVC	0.010	0.015	0.156	19
FA-1804C-1-1N-03	18	4	FPLR	PVC	0.010	0.015	0.181	33
FA-1806C-1-1N-03	18	6	FPLR	PVC	0.010	0.015	0.223	49
FA-2204C-1-1N-03	22	4	FPLR	PVC	0.010	0.015	0.122	15

Show Me
C A B L E S

an INFINIT® brand

www.showmecables.com

888-519-9505 | sales@showmecables.com

Title

Multi-Conductor- Fire Alarm Cable-Low-Voltage-
16 AWG- 2 Conductor- Solid- Unshielded - Riser-
PVC-Red

Part Number

88-207-013

Notes

1. Unless otherwise specified all dimensions are nominal
2. All specifications are subject to change without notice at any time
3. Dimensions are in millimeters