



Product Description

Power limited fire alarm and communications cable for riser or nonriser applications. Fire alarm, smoke detectors, signaling and fire-protective circuits. XX in part number denotes color; call your local sales representative for specific requirements.

Specifications

- CONDUCTOR: Solid or stranded bare copper
- INSULATION: FRPVC
- JACKET: FRPVC with rip cord
- STANDARDS: NEC FPLP, UL Listed
- TEMPERATURE: 75°C

Tech. Info & Standards

PVC
Solid conductor
FPLP, UL Listed

Part No.	Conductor Size AWG	No. of Conductors	Insulation Thickness (in.)	Jacket Thickness (in.)	Nom. O.D. (in.)	Approx. Wt. lb./1,000 ft.
FA-1202C-1-2N-XX	12	2	0.011	0.015	0.238	58
FA-1202C-2-2N-XX	12	2 Stranded	0.011	0.015	0.239	58
FA-1402C-1-2N-XX	14	2	0.011	0.015	0.202	38
FA-1402C-2-2N-XX	14	2 Stranded	0.011	0.015	0.203	38
FA-1404C-1-2N-XX	14	4	0.011	0.015	0.236	71
FA-1602C-1-2N-XX	16	2	0.010	0.015	0.173	26
FA-1604C-1-2N-XX	16	4	0.010	0.015	0.204	48
FA-1802C-1-2N-XX	18	2	0.010	0.015	0.152	18
FA-1802C-2-2N-XX	18	2 Stranded	0.010	0.015	0.154	20
FA-1804C-1-2N-XX	18	4	0.010	0.015	0.177	34
FA-1806C-1-2N-XX	18	6	0.010	0.015	0.240	49
FA-2204C-1-2N-XX	22	4	0.009	0.015	0.122	16

Show Me
C A B L E S

an INFINIT® brand

www.showmecables.com

888-519-9505 | sales@showmecables.com

Title

Multi-Conductor- Fire Alarm Cable-Low-Voltage-
16 AWG- 2 Conductor- Solid- Unshielded -
Plenum

Part Number

88-207-015

Notes

1. Unless otherwise specified all dimensions are nominal
2. All specifications are subject to change without notice at any time
3. Dimensions are in millimeters