

Product Description

- PVC
- Solid conductor
- FPLR, UL Listed

Applications

- For Use With All Power Limited Circuits In Fire Protective Signaling

Specification

- CONDUCTOR: Solid bare copper
- INSULATION: PVC
- JACKET: PVC with rip cord
- STANDARDS: NEC FPLR, UL Listed
- TEMPERATURE: 75°C



Power limited fire alarm and communications cable for riser or nonriser applications. Fire alarm, smoke detectors, signaling and fire-protective circuits. Call your local sales representative for specific requirements.

<u>Part No.</u>	<u>Conductor Size AWG</u>	<u>No. of Conductors</u>	<u>Rating</u>	<u>Insulation</u>	<u>Insulation Thickness (in.)</u>	<u>Overall Jacket Thickness (in.)</u>	<u>Nom. O.D. (in.)</u>	<u>Approx. Wt. lb./1,000 ft.</u>
FA-1202C-1-1N-03	12	2	FPLR	PVC	0.012	0.015	0.264	62
FA-1204C-1-1N-03	12	4	FPLR	PVC	0.012	0.015	0.258	80
FA-1402C-1-1N-03	14	2	FPLR	PVC	0.010	0.015	0.212	40
FA-1404C-1-1N-03	14	4	FPLR	PVC	0.010	0.015	0.252	73
FA-1602C-1-1N-03	16	2	FPLR	PVC	0.010	0.015	0.183	28
FA-1604C-1-1N-03	16	4	FPLR	PVC	0.010	0.015	0.216	49
FA-1802C-1-1N-03	18	2	FPLR	PVC	0.010	0.015	0.156	19
FA-1804C-1-1N-03	18	4	FPLR	PVC	0.010	0.015	0.181	33
FA-1806C-1-1N-03	18	6	FPLR	PVC	0.010	0.015	0.223	49
FA-2204C-1-1N-03	22	4	FPLR	PVC	0.010	0.015	0.122	15

Show Me
C A B L E S

an INFINIT® brand

www.showmecables.com

888-519-9505 | sales@showmecables.com

Title

Multi-Conductor- Fire Alarm Cable-Low-Voltage-
16 AWG- 4 Conductor- Solid- Unshielded - Riser
Rated-PVC-Red

Part Number

88-207-016

Notes

1. Unless otherwise specified all dimensions are nominal
2. All specifications are subject to change without notice at any time
3. Dimensions are in millimeters