		8	7	1	6	1	5		¥	4	. 3	3	1	2	I	1	_
	THE INFORM	ATION CONTAINE F L-COM, INC. AN								REVISION				]			
	WITHOUT THE	WRITTEN PERMISSI	ON OF L-COM, IN	NC. IS PROHIBITED.						ZONE REV		ESCRIPTION		DATE 09/22/2023	CHANGED BY PSRINIVAS	APPROVED DREBECK	-
																	1
D																	D
						4 6			400								
			-	1.210 _ [31] _		.15 [4	°0 1 ─►   ŀ		108 3.15]				1	1.075			
						ני		رحر						[27.3]  - MIN.	_		
					ور <sup>م</sup> د ــــــــــــــــــــــــــــــــــــ												
			∎ If'				ΥL					<u> </u>	[				
С					╗╢							1.224	1				С
									P			[31.1		+			
			.343    ( 34.1]    г					<u> </u>				MIN.					
		Ŀ		USE ONLY 250V FU	USES			Γ <b>Γ</b>		-		A					
							⊧					I					
													PANEL F	IXING DET	AILS		
2						07	·5										
						.07 [2	ĭ -►   ◄	F									
						L	-										
В																	В
	NOTE	S:-															
	1.	CONNECT															
	2. 3.	RATING: 10 FEATURES															
_	5.			ANEL 6.3mm	n QUICK-C	ONNECT											
				BLE FUSEHC													
	4.	PACKAGIN															
				BE INDIVIDU	JALLY PAC	KAGED, LAB	EL		UNLESS OTH DIMENSIONS A	ERWISE SPECIFIED, RE IN INCHES [mm]	APPROVALS	DATE		om	50 High Stree	t, West Mill, er, MA 01845 USA.	1
	5.	PER ILS-10		R REFEREN						ENGTH TOLERANCE: [305] = +1 [25] / -0	DRAWN BY PSRINIVAS	09/22/2023		FINIT <sup>®</sup> brand	Phone: 1.800	0.341.5266 0.682.6936	
А	Э.								>12 [305] ≤60 >60 [1524] ≤120	[1524] = +2 [51] / -0 [3048] = +4 [102] / -0		09/22/2023			RS_PANEL		A
									>120 [3048] ≤300 >300	[7620] = +6 [152] / -0 [7620] = +5% / -0	APPROVED BY DREBECK	09/22/2023			NO_FANEL		
									.X = ± .2 [5]	FRACTIONS	CONFIGURATIO		RODUCT DESCRIF	4 1.5mm PA	NEL SNAP-IN	6.3mm QUICK-	
									.XX = ± .02 [.5] .XXX = ± .005 [.1]	ANGLES ± 1° MAY VAI		ARY C		CONNECT 2	ONNECT 2X FUSEHOLDERS		
									THIRD-ANGLE		COLOR VARIATIONS MAY OCCUR		SIZE CAGE CODE ITEM NO. A 43321 ACM-C4-N15Q6F2			6F2-LC A	
l				I						$\overline{\mathbf{V}}$	I			CAD FILE: ACM-C	4-N15Q6F2-LC.SLDDR		]
	[-Rev.D]	8	7	I	6	I.	5		I	4	3	3	1	2	I	1	