

Construction & Dimensions

CONDUCTOR PARAMETERS	
Number Of Conductors	2
AWG Size	16
Conductor Stranding	19x29
Conductor Type	Bare Copper
Nominal DCR	4.2 Ohm/1000ft
INSULATION PARAMETERS	
Insulation Type	PVC
Insulation Thickness	0.01 in
Insulation Color Code	1. Black 2.Red
SHIELDING PARAMETERS	
Shield Type	Aquaseal Water Blocking Tape
ELECTRICAL CHARACTERISTICS	
Nominal Capacitance Between Conductors	34 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	UV Resistant PVC
Jacket Thickness	0.025 in
Nominal Cable O.D.	0.242 in
Plenum	No
NEC UL Rating	CM, CL3, FPL
RoHS Compliant	Yes
TIA Test	TIA455-82 Water Penetration Test
Pull Tension	55 lbs
Bend Radius	2.178 in
Cable Weight	29 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

Product Photo



Show Me
CABLES

an INFINIT® brand

www.showmecables.com
888-519-9505 | sales@showmecables.com

Title

2 Conductor -16 AWG-Stranded-
Unshielded -Aqsl Water blocking
Tape- PVC- Gray

Part Number

AQC225GY

Notes

1. Unless otherwise specified all dimensions are nominal
2. All specifications are subject to change without notice at any time
3. Dimensions are in millimeters