

Product Photo



Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	4
• AWG Size	22
• Conductor Stranding	Solid
• Conductor Type	Bare copper
• Nominal DCR	17.5Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	PVC
• Insulation Thickness	0.008 in
• Insulation Color Code	1.Black,2.Red,3.White,4.Green
SHIELDING PARAMETER	-
• Shield Type	Aquaseal Water Blocking Tape
ELECTRICAL CHARACTERISTICS	-

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	UV Resistant PVC
Jacket Thickness	0.025 in
Nominal Cable O.D.	0.194 in
Plenum	No
NEC UL Rating	CM, CL3
RoHS Compliant	Yes
TIA Test	TIA455-82 Water Penetration Test
Bend Radius	2.0
Cable Weight	43 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300



www.showmecables.com
888-519-9505 | sales@showmecables.com

Title	4 Conductor -22 AWG-Solid- Unshielded -Aqsl Water blocking Tape- PVC- Gray
Part Number	AQC240GY

Notes
 1. Unless otherwise specified all dimensions are nominal
 2. All specifications are subject to change without notice at any time
 3. Dimensions are in millimeters