



Part Number: 1855A

Serial Digital Coax, Sub-miniature, #23 Solid BC, Foil + 95% TC braid, CMR

Product Description

Low Loss Serial Digital Coax, Riser-CMR, Sub-Miniature 23 AWG solid bare copper conductor, foam HDPE core, Duofoil, +95% tinned copper braid, PVC jacket

Technical Specifications

Product Overview

| | |
|------------------------|--|
| Environmental Space: | Indoor - Riser |
| Suitable Applications: | SMPTE 2081-1 6 Gb/s UHD TV, SMPTE 424M 3 Gb/s HD-SDI 1080P |

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | Nominal Diameter | No. of Coax |
|-----|-----------|------------------|------------------|-------------|
| 23 | Solid | BC - Bare Copper | 0.023 in | 1 |

| | |
|------------------|--------|
| Conductor Count: | 1 |
| Conductor Size: | 23 AWG |

Insulation

| Material | Nominal Diameter |
|---|------------------|
| Gas-injected FHDPE - Foam High Density Polyethylene | 0.102 in |

Outer Shield Material

| Type | Layer | Material | Material Trade Name | Coverage [%] |
|-------|-------|-----------------------------|---------------------|--------------|
| Tape | 1 | Aluminum/Polyester/Aluminum | Duofoil® | 100 % |
| Braid | 2 | TC - Tinned Copper | | 95 % |

Outer Jacket Material

| Material | Nominal Diameter |
|--------------------------|------------------|
| PVC - Polyvinyl Chloride | 0.159 in |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Outer Conductor DCR |
|-----------------------|---------------------|
| 20.1 Ohm/1000ft | 3.7 Ohm/1000ft |

Capacitance

| Nom. Capacitance Conductor to Shield |
|--------------------------------------|
| 16.3 pF/ft |

Inductance

| Nominal Inductance |
|--------------------|
| 0.107 µH/ft |

Impedance

| Nominal Characteristic Impedance |
|----------------------------------|
|----------------------------------|

75 Ohm

Return Loss (RL)

| Frequency [MHz] | Minimum Return (RL) |
|---------------------|---------------------|
| 5 MHz - 1600 MHz | 23 dB |
| 1600 MHz - 4500 MHz | 21 dB |
| 4500 MHz - 6000 MHz | 15 dB |

High Frequency (Nominal/Typical)

| Frequency [MHz] | Nom. Insertion Loss |
|-----------------|---------------------|
| 1 MHz | 0.39 dB/100ft |
| 3.58 MHz | 0.78 dB/100ft |
| 5 MHz | 0.92 dB/100ft |
| 6 MHz | 1.00 dB/100ft |
| 7 MHz | 1.08 dB/100ft |
| 10 MHz | 1.2 dB/100ft |
| 12 MHz | 1.3 dB/100ft |
| 25 MHz | 1.8 dB/100ft |
| 67.5 MHz | 2.83 dB/100ft |
| 71.5 MHz | 2.93 dB/100ft |
| 88.5 MHz | 3.22 dB/100ft |
| 100 MHz | 3.39 dB/100ft |
| 135 MHz | 3.84 dB/100ft |
| 143 MHz | 4.00 dB/100ft |
| 180 MHz | 4.41 dB/100ft |
| 270 MHz | 5.44 dB/100ft |
| 360 MHz | 6.34 dB/100ft |
| 540 MHz | 7.85 dB/100ft |
| 720 MHz | 9.15 dB/100ft |
| 750 MHz | 9.31 dB/100ft |
| 1000 MHz | 10.89 dB/100ft |
| 1500 MHz | 13.38 dB/100ft |
| 2000 MHz | 15.64 dB/100ft |
| 2250 MHz | 16.68 dB/100ft |
| 3000 MHz | 19.65 dB/100ft |
| 4500 MHz | 24.35 dB/100ft |
| 6000 MHz | 28.97 dB/100ft |

Delay

| Nominal Delay | Nominal Velocity of Propagation (VP) [%] |
|---------------|--|
| 1.24 ns/ft | 82 % |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V RMS |

| | |
|------------------------------------|---|
| Electrical Characteristics Notes: | TDR Impedance: 75 +/- 1.5 Ohms |
| Other Electrical Characteristic 2: | Return Loss: Fixed bridge and termination |

Temperature Range

| | |
|-----------------------|----------------|
| UL Temp Rating: | 75°C |
| Operating Temp Range: | -30°C To +75°C |

Mechanical Characteristics

| | |
|----------------------------------|---------------|
| UV Resistance: | Yes |
| Bulk Cable Weight: | 17 lbs/1000ft |
| Max Recommended Pulling Tension: | 33 lbs |
| Min Bend Radius/Minor Axis: | 1.6 in |

Standards

| | |
|--------------------------|-----|
| NEC/(UL) Specification: | CMR |
| CEC/C(UL) Specification: | CMG |

| | |
|----------------|----------------|
| CPR Euroclass: | Eca |
| RG Type: | Mini 59/U Type |

Applicable Environmental and Other Programs

| | |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2004-01-01 |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Suitability

| | |
|------------------------------------|--|
| Suitability - Aerial: | Yes - Black only, when supported by messenger wire |
| Suitability - Burial: | No |
| Suitability - Hazardous Locations: | No |
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | Yes - Black only |

Flammability, LSOH, Toxicity Testing

| | |
|--------------------|-----------------------|
| UL Flammability: | UL1666 Vertical Shaft |
| CSA Flammability: | FT4 |
| UL voltage rating: | 300 V RMS |

Plenum/Non-Plenum

| | |
|----------------|-------|
| Plenum (Y/N): | No |
| Plenum Number: | 1855P |

Part Number

| | |
|----------------|-----------|
| Related Parts: | 1855ABHD3 |
|----------------|-----------|

Variants

| Item # | Color | Footnote |
|----------------|-------------|----------|
| 1855A 0101000 | Black | C |
| 1855A 010500 | Black | |
| 1855A 010N1000 | Black | |
| 1855A 010N1000 | Black | |
| 1855A.00500 | Black | |
| 1855A 0061000 | Blue, Light | C |
| 1855A 006N1000 | Blue, Light | |
| 1855A 006N1000 | Blue, Light | |
| 1855A 0011000 | Brown | C |
| 1855A 001N1000 | Brown | |
| 1855A 001N1000 | Brown | |
| 1855A 0081000 | Gray | C |
| 1855A 008N1000 | Gray | |
| 1855A 008N1000 | Gray | |
| 1855A N3U1000 | Green, Mil | C |
| 1855A N3UN1000 | Green, Mil | |
| 1855A N3UN1000 | Green, Mil | |
| 1855A 0031000 | Orange | C |
| 1855A 003N1000 | Orange | |
| 1855A 003N1000 | Orange | |
| 1855A 0021000 | Red | C |
| 1855A 002N1000 | Red | |
| 1855A 002N1000 | Red | |
| 1855A 0071000 | Violet | C |
| 1855A 007N1000 | Violet | |

| | | |
|----------------|--------|---|
| 1855A 007N1000 | Violet | |
| 1855A 0091000 | White | C |
| 1855A 009N1000 | White | |
| 1855A 009N1000 | White | |
| 1855A 0041000 | Yellow | C |
| 1855A 004N1000 | Yellow | |
| 1855A 004N1000 | Yellow | |

| | |
|-----------|------------------------|
| Footnote: | C - CRATE REEL PUT-UP. |
|-----------|------------------------|

Product Notes

| | |
|--------|---|
| Notes: | Print legend includes sequential footage marks. |
|--------|---|

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.