



# **Product Description**

Surveillance & CCTV Cable, RG11, Rated-CM, 14 AWG solid bare copper, foam polyolefin core, 95% bare copper braid, PVC jacket

# **Technical Specifications**

uitable Application	ns:			Analog Video/CCTV Coax
ysical Char	acteristics (Ov	erall)		
nductor				
WG Stranding	Material	Nominal Diameter	No. of Coax	
1 Solid	BC - Bare Copper	0.066 in	1	
onductor Size:				14 AWG
sulation				
Mat	erial	Nominal Diameter		
Bas-injected FPE -	Foam Polyethylene	0.28 in		
uter Shield Mater	ial		-	
ype Materia		<b>%1</b>		
braid BC - Bare C				
uter Jacket Mater				
Material	Nominal Dia	meter		
VC - Polyvinyl Ch				
	0.463 in			
Veight:				0.46 lbs

### Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance	Nominal Outer Shield DCR	Outer Conductor DCR
2.6 Ohm/1000ft	2.6 Ohm/1000ft	1.2 Ohm/1000ft	1.2 Ohm/1000ft

### Capacitance

Nom. Capacitance Conductor to Shield
16.1 pF/ft

### Inductance

Nominal Inductance 0.106 µH/ft

### Impedance

Nominal Characteristic Impedance
75 Ohm

# High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.17 dB/100ft
10 MHz	0.35 dB/100ft
50 MHz	0.9 dB/100ft
100 MHz	1.3 dB/100ft
200 MHz	1.9 dB/100ft
400 MHz	2.9 dB/100ft
700 MHz	4.1 dB/100ft
900 MHz	4.8 dB/100ft
1000 MHz	5.2 dB/100ft

### Delay

Max. Delay Skew	Nominal Delay	Nominal Velocity of Propagation (VP) [%]
84 ns/100m	1.21 ns/ft	84 %

### Voltage

Non-UL Voltage Rating	UL Voltage Rating
600 V RMS	300 V RMS

# **Temperature Range**

UL Temp Rating:	75°C
Operating Temp Range:	-30°C To +75°C

### **Mechanical Characteristics**

Bulk Cable Weight:	82 lbs/1000ft
Max Recommended Pulling Tension:	144 lbs
Min Bend Radius/Minor Axis:	4 in

# Standards

NEC Articles:	800
NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	СМ
CPR Euroclass:	Eca
RG Type:	11/U Type
Series Type:	Series 11

# Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	Yes
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

# Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes - Black only

# Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT1
UL voltage rating:	300 V RMS

# Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	613948

### **Part Number**

# Item # Color Footnote 513945.00300 Black 513945.010100 Black 513945.010100 Black C

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.