

8205MN Multi-Conductor - SpaceMaker Audio, Control and Instrumentation Cable



For more Information
please call

1-800-Belden1



General Description:

20 AWG stranded (26x34) tinned copper conductors, Polypropylene insulation, twisted pairs, PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
1	20	26x34	TC - Tinned Copper

Total Number of Conductors: 2

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
PP - Polypropylene	0.254

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.406

Overall Cable

Overall Cabling Color Code Chart:

Number	Color
1	Black
2	White

Overall Nominal Diameter: 3.708 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +80°C

Bulk Cable Weight: 16.370 Kg/Km

Max. Recommended Pulling Tension: 124.550 N

Min. Bend Radius/Minor Axis: 14.732 mm

Min. Bend Radius (Continuous Flexing): 37.084 mm

Flex Cycle Rating: 1 Million Flexes

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

METRIC MEASUREMENT VERSION

8205MN Multi-Conductor - SpaceMaker Audio, Control and Instrumentation Cable

Other Specification: UL Style AWM 2937 (300V 80C), NFPA 79

Flame Test

CSA Flame Test: FT2

Electrical Characteristics (Overall)

Nom. Inductance:

Inductance (µH/m)
0.085

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
47.246

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
34.122

Max. Operating Voltage - UL:

Voltage
300 V RMS

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8205MN 004100	100 FT	2.600 LB	YELLOW		2 #20 PO PVC
8205MN 0041000	1,000 FT	13.000 LB	YELLOW		2 #20 PO PVC
8205MN 006100	100 FT	2.600 LB	BLUE, LIGHT		2 #20 PO PVC
8205MN 0061000	1,000 FT	13.000 LB	BLUE, LIGHT		2 #20 PO PVC
8205MN 008100	100 FT	2.600 LB	GRAY		2 #20 PO PVC
8205MN 0081000	1,000 FT	13.000 LB	GRAY		2 #20 PO PVC

Revision Number: 0 Revision Date: 09-29-2016

© 2016 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).