


REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
Α	INITIAL RELEASE	07/19/2022	GUTTADAURO





"P1" 3.5 FEMALE **AUDIO** 



## NOTES:

- 1. ELECTRICAL TEST:
  - a. 100% OPEN SHORT MIS-WIRE TEST.
  - b. CONTACT RESISTANCE: 5 OHM MAX.
  - c. INSULATION RESISTANCE: 5M OHM MIN.
  - d. HI-POT TEST: DC 300V/10ms.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS

## TOLERANCES:

.X = ±.2 [5.08] FRACTIONS  $.XX = \pm .02 [.51]$ ± 1/32 .XXX = ±.005 [.13] ANGLES ± 1°

## CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0

ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY



## an INFINIT® brand

115 Chesterfield Industrial Blvd., Chesterfield, MO 63005

Phone: 1.888.519.9505 Fax: 1.888.519.9515 Website: www.ShowMeCables.com

E-mail: CustomerService@ShowMeCables.com ITEM NO. SIZE CAGE CODE DRAWN BY Α

THIRD-ANGLE PROJECTION



THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF SHOWMECABLES, INC ALL RIGHTS RESERVED.

SCALE N/A

REV 3SVT8 **DZINN** CAUC35MMAD Α

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.