

Passive CWDM, Single LGX Mux, 8 Ch w/ 20nm spacing, start ch 1470nm, LC/UPC w/ MON (1%)&Pass Single Fiber



## CWM-08347-00461L

### Features

- Passive
- CWDM
- 20nm spacing
- Standard LGX cassette
- Single Fiber Mux
- 8 Channels
- Starting with channel 1471nm
- LC/UPC connectors
- 1% Monitor option
- Pass / Express option

### Applications

- Single Mode Fiber Networking
- Single Fiber
- Mux function
- Metro transport
- Regional Distribution
- Inside Plant (ISP) Operation

### Description

The CWM-08347-00461L is a CWDM Passive Filter with 8 CWDM Channels. The CWM-08347-00461L is a single HU LGX cassette filter with Mux functionality. The CWM-08347-00461L has 8 channels: 1471, 1491, 1511, 1531, 1551, 1571, 1591, and 1611nm, starting with 1471nm and with 20nm spacing. The CWM-08347-00461L has LC/UPC connectors and has Monitor port option and a PASS port to carry the unused CWDM channels through. The CWM-08347-00461L is a single fiber filter for sending channels muxed into a COM signal. produces the high quality passive filters that your business can rely on. With products continually in stock and same-day shipping, our expert technical support and knowledgeable sales team can get you to the right parts for the job.

### Configuration

Connector Type	LC/UPC
Number of Channels	8
Module Function	Mux
Filter Type	CWDM

### Filter Specifications

Description	Minimum	Typical	Maximum	Units
Operating Wavelength	1260		1635	nm
Pass Port Wavelength	1271		1611	nm
Pass Port Insertion Loss			1.8	dB
Pass Port Isolation	12			dB
Pass Band	6.5			nm
Pass Band Ripple			0.5	dB
Center Wavelength (Channel)	1471		1611	nm
Channel Spacing		20		nm
Channel Insertion Loss			2	dB
Return Loss	45			dB
Directivity			50	dB
PDL			0.25	dB
PMD			0.2	PS
Power Handling			300	mW

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[Passive CWDM, Single LGX Mux, 8 Ch w/ 20nm spacing, start ch 1470nm, LC/UPC w/ MON \(1%\)&Pass Single Fiber](#)

Passive CWDM, Single LGX Mux, 8 Ch w/ 20nm spacing, start ch 1470nm, LC/UPC w/ MON (1%)&Pass Single Fiber



Channel to Monitor Port IL	25	dB
COM to Monitor Port IL	23	dB
IL Thermal Stability	0.005	dB/degC
Wavelength Thermal Stability	0.002	nm/degC

**Environmental Specifications**

**Temperature**

Operating Range -20 to +65 deg C

Storage Range -40 to +85 deg C

Humidity 5-98 %RH

**Compliance Certifications** (see [product page](#) for current document)

**Plotted and Other Data**

Notes:

Passive CWDM, Single LGX Mux, 8 Ch w/ 20nm spacing, start ch 1470nm, LC/UPC w/ MON (1%)&Pass Single Fiber from Show Me Cables has same day shipment for domestic and International orders. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications.

URL: <https://www.showmecables.com/passive-cwdm-single-lgx-mux-8-ch-w-20nm-spacing-start-ch-1470nm-lc-upc-w-mon-1-pass-single-fiber-pcw1m-08347-nn46-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Show Me Cables reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Show Me Cables does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Show Me Cables does not assume liability arising out of the use of any part or document.

Passive CWDM, Single LGX Mux, 8 Ch w/ 20nm spacing, start ch 1470nm, LC/UPC w/ MON (1%)&Pass Single Fiber

**CWM-08347-00461L CAD Drawing**

