


Passive CWDM, Field Unit Barrel OADM, 1 Channel 20nm
1610nm, 2m 250um colored bare fiber, Pass Port



CWO-12061-2403

Features

- Passive
- CWDM
- 20nm spacing
- Barrel filter (34mmx5.5mm)
- Single channel OADM
- CWDM 1611nm
- 2m 250um colored fiber leads
- Pass fiber for unused CWDM channels
- Industrial temperature (-40c ~ 85c)

Applications

- Single Mode Fiber Networking
- Single Fiber
- Single channel OADM function
- Metro transport
- Regional Distribution
- Outside Plant (OSP) Operation

Description

The CWO-12061-2403 is a CWDM Passive Filter with 1 Channel OADM. The CWO-12061-2403 is a 34x5.5mm barrel filter with add a single channel to a composite signal or remove a single channel from a composite signal. The CWO-12061-2403 is rated for industrial temperature function (-40c to +85c) for applications such as outside plant installation. The CWO-12061-2403 has single channel 1611nm Add/Drop with other channels being passed. The CWO-12061-2403 has 2 meter 250um colored fiber leads. The CWO-12061-2403 is a single fiber filter for adding or removing a single wavelength from a COM signal. and are used in pairs for implementations using two fibers. ShowMeCables produces the high quality passive filters that your business can rely on. With products continually in stock and same-day shipping, our expert technical support and knowledgeable sales team can get you to the right parts for the job.

Configuration

Connector Type	250um Bare Fiber (2M)
Number of Channels	1
Module Function	OADM
Filter Type	CWDM

Filter Specifications

Description	Minimum	Typical	Maximum	Units
Operating Wavelength	1260		1620	nm
Pass Band	6.5			nm
Pass Band Insertion Loss			1	dB
Pass Band Ripple			0.5	dB
Channel Spacing		20		nm
Return Loss	45			dB
Directivity			50	dB
PDL			0.15	dB
PMD			0.15	PS
Power Handling			300	mW
Adjacent Channel Isolation	30			dB
Non-Adjacent Channel Isolation	45			dB
Reflect Channel Isolation	12			dB
Reflect Band Insertion Loss			0.8	dB

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Passive CWDM, Field Unit Barrel OADM, 1 Channel 20nm 1610nm, 2m 250um colored bare fiber, Pass Port](#)

Passive CWDM, Field Unit Barrel OADM, 1 Channel 20nm
1610nm, 2m 250um colored bare fiber, Pass Port



Environmental Specifications

Temperature

Operating Range

-40 to +85 deg C

Storage Range

-40 to +85 deg C

Humidity

5-95 %RH

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Passive CWDM, Field Unit Barrel OADM, 1 Channel 20nm 1610nm, 2m 250um colored bare fiber, Pass Port from Show Me Cables has same day shipment for domestic and International orders. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications.

URL: <https://www.showmecables.com/No-URL-Convention-Found-for-?CWO-12061-2403-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Show Me Cables reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Show Me Cables does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Show Me Cables does not assume liability arising out of the use of any part or document.

CWO-12061-2403 CAD Drawing

