



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	01/19/2022	GUTTA DAURO



P1  
DISPLAYPORT 2.0  
MALE  
CONNECTOR

P2  
DISPLAYPORT 2.0  
MALE  
CONNECTOR





ITEM NUMBER	LENGTH MM [FT]
DP20Z-MM-BLK-05M	500.0 +51.0/-0 [1.64]
DP20Z-MM-BLK-1M	1000.0 +51.0/-0 [3.28]
DP20Z-MM-BLK-2M	2000.0 +102.0/-0 [6.56]
DP20Z-MM-BLK-3M	3000.0 +102.0/-0 [9.84]

**NOTES:**

- VOLTAGE TEST: DC 300V 10MS  
INSULATION RESISTANCE: 5.0M ohm/min.  
CONDUCTANCE RESISTANCE: 5.0 ohm/max.
- DUST CAPS INSTALLED AT SHIPPING. (NOT SHOWN)
- CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
- CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

**REGULATORY COMPLIANCE:**

EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0 ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 [5]      FRACTIONS ± 1/32 .XX = ±.02 [.5]      ANGLES ± 1° .XXX = ±.005 [.13]	APPROVALS	DATE	 50 High Street, West Mill, North Andover, MA 01845 USA. Phone: 1.800.341.5266 1.978.682.6936
	DRAWN BY DFRISIELLO	01/19/2022	
CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY	CHECKED BY DGUST	01/19/2022	PRODUCT DESCRIPTION DisplayPort 2.0 Assembly, M/M, LSZH, BLK
THIRD-ANGLE PROJECTION 	APPROVED BY GUTTA DAURO	01/19/2022	SCALE: NONE    CAD FILE: DP20Z-MM-BLK.SLDDRW    SHEET 1 OF 1
COLOR VARIATIONS MAY OCCUR	SIZE A	CAGE CODE 43321	ITEM NO. DP20Z-MM-BLK