



an INFINIT® brand

14x12x06 Polycarbonate Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120VAC MNT PLT, Solid State Power Saver Controlled Dual Fans Dark Gray



NEMA Enclosures Technical Data Sheet

NBPC141206-10FSD

Features

- High-Impact, UV Resistant Polycarbonate (Dark Gray)
- Stainless steel latches with padlock eye
- NEMA Type 3R / IP24 rated
- Fully gasketed vented lid with filters & user installed wall mounting brackets
- Features aluminum mounting plate with surge protected duplex 120 VAC outlets & solid state power saver controlled Dual-Fan Control, each fan set to different temperature settings

Applications

- Remote Wireless LAN WiFi equipment installations
- Indoor and outdoor installations
- Rapid Deployment Installations
- Corrosive environments & hotspot applications
- Protection of equipment from theft or damage

Description

The box is a rugged weatherproof enclosure that is ideal for both indoor and outdoor applications. Constructed from High-Impact, UV Resistant Polycarbonate material that provides superior durability to impacts and ease of modification while maintaining minimum weight. It is well suited for high temperature or corrosive environments. The lid includes two vents with installed rain guards and filters. The included wall mount brackets come uninstalled and bagged with their hardware inside of the enclosure. Once the brackets are installed the enclosure can be mounted directly to any flat wall surface provided proper screws are used into secure studs. The brackets, once installed, also allow you to use our HGX-PMT pole mount kits. The lid features a non-metallic hinge system that allows for quick removal & can be reattached just as quickly without the need for any tools. The enclosure comes with a pair of stainless-steel latches with padlock eyes allowing you to secure the enclosure from tampering. The enclosure comes in a Dark Gray (Pantone 422C)

Mounting Plate

The aluminum mounting plate included with the NBPC141206-10FSD features standard surge protected duplex 120 VAC outlets and a terminal block for easy hook up to the externally provided line power. The enclosure also features holes for two N-Bulkhead Lightning Protectors or Connectors, a grounding lug and cable conduit connector.

Cooling

To help ensure trouble-free operation of electronic equipment, proper operating temperatures inside an enclosure need to be controlled. With the built-in dual cooling fans, internal temperatures can be better maintained. This model is ideal in Hot environments.

The "Power Saver" feature is designed to reduce electrical usage as well as extend the life of the fans which are controlled by our exclusive dual fan solid state controller. The relays provide independent control for each of the fans with two different turn-on temperatures. The relays also feature Zero Cross Detection for EMI reduction.

For cooling, the NBPC141206-10FS comes with two independently controlled 120 VAC 16.4W (32.8W total) cooling fans installed. The high airflow, low noise fans used allow warm air to be actively pushed out the top vent while the second fan on the lower vent when it turns on actively pulls in outside air into the enclosure. Filters for both ports prevent foreign objects or debris from entering the enclosure. The controller features improved temperature set point accuracy. The top fan has a turn-on temperature of 90° F (32° C). If the temperature continues to climb to 100°F (38°C), the lower fan turns on. When the temperature drops back to 91° F (33° C), the lower fan turns off. When the temperature drops to 81°F (27°C), the top fan turns off. The dual fan design offers energy efficiency. The cooling fans do not require the use of any of the AC outlets, leaving them all available for your equipment.

The HGX-PMT series of pole mounting kits allow the populated enclosure to be securely mounted to a variety of different size poles.

Compatible versions include HGX-PMT13, HGX-PMT16, HGX-PMT28, HGX-PMT29, HGX-PMT30, & HGX-PMT33

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [14x12x06 Polycarbonate Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120VAC MNT PLT, Solid State Power Saver Controlled Dual Fans Dark Gray NBPC141206-10FSD](#)



an INFINITE® brand

14x12x06 Polycarbonate Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120VAC MNT PLT, Solid State Power Saver Controlled Dual Fans Dark Gray



NEMA Enclosures Technical Data Sheet

NBPC141206-10FSD

Size

Outer Height	14.6 in	[370.84 mm]
Outer Width	12.6 in	[320.04 mm]
Outer Depth	7.4 in	[187.96 mm]
Inner Height	13.7 in	[347.98 mm]
Inner Width	11.7 in	[297.18 mm]
Inner Depth	5.9 in	[149.86 mm]
Weight	10.5 lbs	[4.76 kg]
Enclosure Material	Polycarbonate	

Environmental Specifications

Temperature Rating	-40° to 265° F [-40° to 129° C]
NEMA Rating	3R
Ingress Protection (IP) Rating	IP24

Compliance Certifications

UL Listed	No
-----------	----

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [14x12x06 Polycarbonate Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120VAC MNT PLT, Solid State Power Saver Controlled Dual Fans Dark Gray NBPC141206-10FSD](https://www.l-com.com/nema-enclosures-14x12x06-polycarb-weatherproof-nema-3r-encl-120vac-mnt-plt-solid-state-pwr-svr-cntrl-fans-drk-gray-p.aspx)

URL: <https://www.l-com.com/nema-enclosures-14x12x06-polycarb-weatherproof-nema-3r-encl-120vac-mnt-plt-solid-state-pwr-svr-cntrl-fans-drk-gray-p.aspx>


NBPC141206-10FSD CAD Drawing

14x12x06 Polycarbonate Weatherproof Outdoor IP24 NEMA 3R Enclosure,
120VAC MNT PLT, Solid State Power Saver Controlled Dual Fans Dark Gray



REV	DESCRIPTION	DATE	CHANGES BY
A	INITIAL RELEASE	05/15/2019	JMMARTINEZ

1 2 3 4 5 6 7 8


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION OF ANY PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.



VIEW B-B



DETAIL A
2 PLACES



APPROVALS	DATE	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES (MM)
APPROVED BY	04/29/2019	DIMENSIONAL TOLERANCES
DRAWN BY	04/29/2019	FRACTIONAL .XX = ±0.01 [254]
DESIGNED BY	04/29/2019	DECIMAL .XXX = ±0.005 [127]
APPROVED BY	04/29/2019	ANGULAR TOLERANCES: ALL = ±1°
DESIGNED BY	04/29/2019	CONFIGURATIONS OF ALL OF UNDESIGNED FEATURES MAY VARY
APPROVED BY	04/29/2019	COLOR VARIATIONS MAY OCCUR

SECTION C-C

NOTES:

- ENCLOSURE MATERIAL-LIGHT GRAY (PANTONE 422C)
HIGH-IMPACT, UV RESISTANT POLYCARBONATE.
- TEMPERATURE RANGE: -40°F TO 265°F
- CABINETS ARE MAINTENANCE FREE AND CORROSION RESISTANT.
- ALL BE PACKAGED AS PER L-COM SPEC
- ALL DIMENSIONS FOR REFERENCE ONLY.

L-com Global Connectivity	50 HIGH STREET NORTH ANDOVER, MA 01845
CATEGORY	ENCLOSURE
PRODUCT DESCRIPTION	ENCL PC 14x12x06" w/Pwr Saver SS Dual-Fan 120VAC Plt
SECNO	DWG. NO.
B	43321
REV	A
SCALE: 1:1	CAD FILE: NBPC141206-10FSD3D.DWG
SHEET 1 OF 1	