

Low PIM Rated 698-960 MHz + 1710-2700 MHz + 3400-4200 MHz 5 to 7 dBi  
VH-pol MIMO Wall Mount Panel Antenna, 2 x 4.3-10 Female Connector



## EC742IFP07VH-PIM-NF

### Features

- Low Passive Intermodulation (PIM) <-153 dBc @ 2x20W
- Vertical + Horizontal Polarization
- Low return loss, stable performance
- 2 x Type N Female connector for long lasting consistent results
- Covers 5G, WiFi and LTE frequency bands including extended CBRS

### Applications

- Indoor distribution of 5G, LTE, GSM/CDMA
- In-building public or private networks
- LPWAN, LoRA, LTE-M, NB-IoT, IoT, M2M applications
- MIMO DAS (Distributed Antenna Systems)
- Wall Mounts

### Description

The ShowMeCables EC742IFP07VH-PIM-NF is a low PIM rated, high performance wall mount MIMO panel antenna with 5-7 dBi gain. It is specifically designed for in-building wireless networks such as DAS (Distributed Antenna Systems). ShowMeCables's EC742IFP07VH-PIM-NF can be used to distribute Cellular and WiFi signals throughout a building or area. The EC742IFP07VH-PIM-NF operates from 698 to 4200 MHz which is ideal for 5G, LTE, CDMA, LPWAN/IoT/M2M applications including LoRA, LTE-M, and NB-IOT. The Multi-Band design of the ShowMeCables EC742IFP07VH-PIM-NF antenna eliminates the need to purchase different antennas for each frequency. This simplifies installations since the same antenna can be used for a wide array of in-building wireless applications where wide coverage is desired.

The EC742IFP07VH-PIM-NF from ShowMeCables has directional 75 degree typical patterns with V/H polarization and features Type N connectors. The key to providing the best performance in telecommunications is to ensure the components used are low PIM rated. This helps meet the increasing demand for higher data rates and the ability to provide streaming video for mobile devices. With a low PIM rating of <-150 dBc, the 698-4200 MHz EC742IFP07VH-PIM-NF helps meets the most demanding PIM requirements for 5G and LTE/4G bands.

The PIM rated Type N 7 dBi EC742IFP07VH-PIM-NF antenna from ShowMeCables is designed specifically for in-building operation and is ideal for use in large open areas such as indoor courtyards, indoor sporting venues, convention centers and shopping malls. Urgency is in our DNA and this 5G Cellular antenna is in stock and ready to ship same day.

### Configuration

Design	Panel
Band Type	Wide
Radiation Pattern	Directional
Polarization	Vertical/Horizontal
Connector Type	N Female
Interface 2	N Female
Number of Ports	2

### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	698		4200	MHz
Input VSWR			2:1	
Impedance		50		Ohms
Gain		5		dBi
Gain			7	dBi
Input Power			100	Watts

Low PIM Rated 698-960 MHz + 1710-2700 MHz + 3400-4200 MHz 5 to 7 dBi  
VH-pol MIMO Wall Mount Panel Antenna, 2 x 4.3-10 Female Connector



## EC742IFP07VH-PIM-NF

Passive Intermodulation -153  
3rd Order, 2 x 20 W

### Specifications by Band

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	0.698 to 0.806	0.806 to 0.96	1.71 to 2.7	3.4 to 4.2		GHz
Gain	5	6	7	7		dBi
Horizontal HPBW	80	80	65	35		Degrees
Vertical HPBW	73	70	60	30		Degrees
VSWR Max	2:1	2:1	2:1	2:1		

### Mechanical Specifications

Radome Material	PVC
<b>Size</b>	
Length	15.75 in [400.05 mm]
Width	7.09 in [180.09 mm]
Height	2.44 in [61.98 mm]
Weight	3.3 lbs [1.5 kg]

### Environmental Specifications

<b>Temperature</b>	
Operating Range	-55 to +60 deg C
Humidity	< 95

### Plotted and Other Data

Notes:

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Show Me Cables reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Show Me Cables does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Show Me Cables does not assume liability arising out of the use of any part or document.

Low PIM Rated 698-960 MHz + 1710-2700 MHz + 3400-4200 MHz 5 to 7 dBi VH-pol MIMO Wall Mount Panel Antenna, 2 x 4.3-10 Female Connector

EC742IFP07VH-PIM-NF CAD Drawing

