

5

LENGTH METER [FEET]							
2.0 [6.56]							
5.0 [16.40]							
10.0 [32.81]							
15.0 [49.21]							

B

## <u>NOTES:</u>

8

В

А

T-Rev.D

- 1. FC CONNECTOR 1 ASSEMBLY POLISH TYPE: UPC.
- 2. ST CONNECTOR 1 ASSEMBLY POLISH TYPE: UPC.
- 3. ALL CONNECTORS ACCOMPANIED WITH A DUST CAP INSTALLED (NOT SHOWN).
- 4. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED.

## **REGULATORY COMPLIANCE:**

EU ROHS DIRECTIVE (MOST RECENT RELEASED VERSION).

6

7

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]	APPROVALS	DATE					50 High Stree North Andov			
OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0	drawn by K.GLEBOVA	04/18/22		_	_	brand	Phone: 1.80	0.341.5 8.682.6		
>12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0	CHECKED BY P.HOSPODAR	04/25/22	CATEGO	RY						A
>120 [3048] <300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0	APPROVED BY P.HOSPODAR	04/25/22	FIBER OPTICS							
ALL OTHER DIMENSIONAL TOLERANCES:           .X = ± .2 [5]         FRACTIONS           .XX = ± .02 [.5]         ± 1/32           .XXX = ± .005 [.13]         ANGLES ± 1°	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		FIBER OPTIC PATCH CORD MM OM2 SIMPLEX 3mm FC/UPC-ST/UPC ARMORED LSZH, BLACK							
THIRD-ANGLE PROJECTION $( \oplus ) - ( - )$	COLOR VAR MAY OC		SIZE A	CAGE 0	321		CA-M2FC	-STS	RE A	v. <b>\</b>
$\rightarrow$ $\rightarrow$			SCALE: NONE CAD FILE: FCA-A			ILE: FCA-M2FC-S	2FC-STS.SLDDRW		SHEET 1 OF	1
<b>↑</b> 4	3		I		2		1	1		