
	8	7	6	5	4		3	2		l	
	THE INFORMATION CONTAINE	D IN THIS DRAWING IS THE SO	LE					REVISIONS			
	PROPERTY OF L-COM, INC. AN	Y REPRODUCTION IN PART OR W	HOLE			REV		DESCRIPTION	DATE	APPROVED	
	WITHOUT THE WRITTEN PERMISSI	ON OF L-COM, INC. IS PROHIBITE	D.			А	INITIAL RELEASE		7/14/22	PHOSPODAR	
D											
											D

FIBER COUN	4								
FIBER TYPE	MULTI MODE								
	OD (mm)	6.0 ± 0.3							
CABLE	MATERIAL	LSZH							
	COLOR	BLACK							
PBT LOOSE TUBE	OD (mm)	3.1 ± 0.1							
MAX TENSILE STRENGTH	SHORT-TERM	1000							
(N)	LONG-TERM	400							
MAX CRUSH RESISTANCE	SHORT-TERM	800							
(N/100mm)	LONG-TERM	300							
STRENGTH MEM	BERS	GLASS YARN							
		850nm ≤ 3.5							
ATTENUATION	dB/kM	1300nm ≤ 1.5							
BANDWIDT	4	Mhz km							
50/125 µm	850nm ≥ 200	1300nm ≥ 200							
PROOF TEST	kpsi	≥ 100							

С

В



С

B

