



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SHOW ME CABLES, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SHOW ME CABLES, INC. IS PROHIBITED.

REVISION					
ZONE	REV.	DESCRIPTION	DATE	CHANGED BY	APPROVED BY
	A	INITIAL RELEASE	01/24/2023	DMAY	DGUTTADAURO



WIRING DIAGRAM



PART NUMBER	LENGTH	
	FEET	METERS
M12A4PVC-FF-3	3	0.9 ± .02
M12A4PVC-FF-6	6	1.8 ± .04
M12A4PVC-FF-10	10	3.0 ± .05

- NOTE:**
- ELECTRICAL TEST:
 - 100% OPEN SHORT MISWIRE TEST.
 - INSULATION RESISTANCE: 10M OHM MIN, 300V/DC.
 - CONDUCTOR RESISTANCE: 3 OHM MAX.
 - OPERATING TEMPERATURE RANGE: -20°C~80°C.
 - WATERPROOF IP67.
 - CABLE ASSEMBLIES TO BE TESTED FOR CONTINUITY.
 - CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED.

REGULATORY COMPLIANCE:
EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0 ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 [5] FRACTIONS ± 1/32 .XX = ± .02 [5] ANGLES ± 1° .XXX = ± .005 [1.3]	APPROVALS	DATE	 115 Chesterfield Industrial Blvd., Chesterfield, MO 63005 Phone: 1.888.519.9505 Fax: 1.888.519.9515
	DRAWN BY DMAY	01/24/2023	
CHECKED BY HBAKKE	01/24/2023	PRODUCT DESCRIPTION M12 4 POSITION A-CODE, PVC JACKET, FEMALE/FEMALE	
APPROVED BY DGUTTADAURO	01/24/2023	SIZE A	CAGE CODE 3SVT8 ITEM NO. M12A4PVC-FF REV. A
THIRD-ANGLE PROJECTION 	COLOR VARIATIONS MAY OCCUR	SCALE: NONE	CAD FILE: M12A4PVC-FF.SLDDRW
		SHEET 1 OF 1	