



| WIRING MAP |        |      |
|------------|--------|------|
| "P1"       | COLOR  | "P2" |
| 1          | WHITE  | 1    |
| 2          | BLACK  | 2    |
| 3          | RED    | 3    |
| 4          | GREEN  | 4    |
| 5          | YELLOW | 5    |
| 6          | BLUE   | 6    |

**NOTES:**

**MATERIAL:**

PLUG HOUSING: POLYCARBONATE, CLEAR, UL94V-0  
 CONTACTS: PHOSPHOR BRONZE  
 JACKET: OUTDOOR AND DIRECT BURIAL

**FINISH:**

CONTACTS: 50 μINCHES GOLD IN CONTACT AREA  
 OVER 100 μINCHES NICKEL PLATE OVERALL.

**CABLE CHARACTERISTICS:**

6 CONDUCTOR ROUND CABLE, OUTDOOR AND DIRECT BURIAL  
 U.L. STYLE 20251, 26 AWG STRANDED

UNLESS OTHERWISE SPECIFIED,  
 DIMENSIONS ARE IN INCHES (mm)

TOLEANCES TO BE:  
 .X ± .1 (2.5) ANGLES ±2°  
 .XX ± .01 (.25)  
 .XXX ± .005 (.13)



|                             |          |                         |      |              |  |
|-----------------------------|----------|-------------------------|------|--------------|--|
| CATEGORY                    |          |                         |      | MODULAR      |  |
| PRODUCT DESCRIPTION         |          |                         |      |              |  |
| ROUND CABLE, (6X6) STRAIGHT |          |                         |      |              |  |
| SIZE                        | TSCM NO. | DWG. NO.                | REV. |              |  |
| A                           | 43321    | TDC057                  | C    |              |  |
| SCALE: NONE                 |          | CAD FILE: TDC007.S.DDRW |      | SHEET 1 OF 1 |  |