
	REVISIONS			
	REV.	DESCRIPTION	DATE	APPROVED
	Α	INITIAL RELEASE	4/12/2021	SELLIS
	В	ADD PIM LABEL, UPDATE NOTES	7/12/21	SRAUTUS



NOTES:

- CABLES 84" AND UNDER HAVE 1 LABEL CENTERED. CABLES OVER 84" HAVE 2 LABELS, ONE AT EACH END 12" FROM THE FRONT OF THE CONNECTOR.
- PIM LABEL 6" FROM CABLE END 1 PLACE.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

 $.X = \pm .2$ [5.08] FRACTIONS $.XX = \pm .02 [.51]$ ± 1/32 .XXX = ±.005 [.13] | ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0

300 [7620] < L = +5%L / -0 ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY

PASTERNACK an INFINIT® brand

Pasternack Enterprises, Inc. P.O.Box 16759, Irvine, CA 92623. Phone: 1.949.261.1920 | 1.866.727.8376 Fax: 1.949.261.7451

Website: www.pasternack.com E-mail: sales@pasternack.com SHEET SCALE N/A

THIRD-ANGLE PROJECTION

THE INFORMATION AND

DESIGN IN THIS DOCUMENT

IS THE PROPERTY OF

PASTERNACK CORPORATION

ALL RIGHTS RESERVED.

SIZE CAGE CODE DRAWN BY ITEM NO. REV Α 53919 DMAY PE3C8001 В

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.