


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISION					
ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	INITIAL RELEASE	07/27/2023	LNAGARAJ	RCARLESCO

USB 2.0 TYPE C-MALE

USB 2.0 TYPE A-FEMALE



PIN ASSIGNMENT



P1 (TYPE C/M)	COLOR	P2(USB2.0/F)
A4 A9 B4 B9	RD	1
A7	WT	2
A6	GN	3
A1 A12 B1 B12	BK	4

TEST CONDITIONS:

- 100% OPEN, SHORT AND SWAP TEST.
- ON-RESISTANCE: 2 OHMS MAX.
- INSULATION RESISTANCE: 10 MEGAOHM MIN/DC300V/10MS (WIRE END).
- 100% MACHINE TEST, THROUGH THE LAPTOP TEST (USB C PLUG DOUBLE-SIDED TEST), WITH A SPECIAL USB TEST HEAD TO TEST, WHETHER THE FUNCTION REACHES 480MBPS.

NOTE:

- CABLE: USB 2.0, PVC JACKET.
- ALL MARKINGS ARE FOR REFERENCE ONLY.
- PRODUCT SHALL BE INDIVIDUALLY PACKAGED.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0 ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 [5] FRACTIONS ± 1/32 .XX = ± .02 [5] ANGLES ± 1° .XXX = ± .005 [13]	APPROVALS DRAWN BY LNAGARAJ CHECKED BY RCARLESCO APPROVED BY GUITADAURO	DATE 07/27/2023 07/28/2023 07/28/2023	 50 High Street, West Mill, North Andover, MA 01845 USA. Phone: 1.800.341.5266 1.978.682.6936	
	THIRD-ANGLE PROJECTION 	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY COLOR VARIATIONS MAY OCCUR		CATEGORY USB C DOCKS
SIZE A		CAGE CODE 43321	ITEM NO. USBCA2	REV. A
SCALE: NONE		CAD FILE: USBCA2.SLDDRW		SHEET 1 OF 1