



AQ246

14/4 Unshielded AQUASEAL Direct Burial CL3/FPL Rated
Audio, Control, Alarm Direct Burial



Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	4
• AWG Size	14
• Conductor Stranding	19x27
• Conductor Type	Bare copper
• Nominal DCR	2.7 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	PVC-Nylon
• Insulation Thickness	0.02 in
• Insulation Color Code	1.Black,2.Red,3.Blue ,4.Brown
SHIELDING PARAMETER	-
• Shield Type	Aquaseal Water Blocking Tape
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	32 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	UV Resistant PVC
Jacket Thickness	0.04 in
Nominal Cable O.D.	0.395 in
Plenum	No
NEC UL Rating	CL3, FPL, PLTC
RoHS Compliant	Yes
TIA Test	TIA455-82 Water Penetration Test
Pull Tension	164 lbs
Bend Radius	3.555 in
Cable Weight	99 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 90 Deg C

Detailed Specification & Technical Data



AQ246

14/4 Unshielded AQUASEAL Direct Burial CL3/FPL Rated
Audio, Control, Alarm Direct Burial



Related Products

RELATED PRODUCTS	-
Plenum Number	25246B
Non Plenum Number	246
Aquaseal Direct Burial Number	AQ246