



**HA210**

2 Conductor 10AWG Unshielded CL2 Rated  
Large Venue Speaker Distribution

**Construction & Dimensions**

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	2
• AWG Size	10
• Conductor Stranding	65x28
• Conductor Type	Bare copper
• Nominal DCR	1.1 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Polypropylene - PP
• Insulation Thickness	0.012 in
• Insulation Color Code	1. Black 2.White
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-

**Overall Construction**

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thickness	0.025 in
Nominal Cable O.D.	0.257 in
Plenum	No
NEC UL Rating	CL2
RoHS Compliant	Yes
Pull Tension	250 lbs
Bend Radius	2.313 in
Cable Weight	83 lbs

**Overall Electrical & Optical Characteristics**

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300



**HA210**

2 Conductor 10AWG Unshielded CL2 Rated  
Large Venue Speaker Distribution

**Related Products**

RELATED PRODUCTS	-
Plenum Number	25210